

## 1K Spray

Endura 1K Spray is Endura one component coatings packaged in easy to use aerosol.

### Product Features

- ◆ Professional spray gun quality results
- ◆ Easy to Use
- ◆ No mess or measuring
- ◆ No equipment needed

### Theoretical Solids

#### Content:

Volume: N/A  
Depending on product,  
please see specific product  
TDS for more information

### Shelf Life\*

(3) Three Years

### Pot Life Product:

12 Hours @ 77°F (25°C)  
and 50% RH



### Suitability

Endura 1K spray is a high performance coating excellent for repairs, or for painting smaller projects.

Please read the technical Data Sheet for the specific product being sprayed for additional important suitability and surface preparation information.

### Current Endura 1K products

Endura 1K aerosols are currently available in the following products:

- ◆ V-Link
- ◆ P-Link
- ◆ Lucent

### Using Endura 1K Spray

Shake can vigorously for 2 minutes minimum (after mixing ball rattles) before using.

### Environmental Conditions

For optimum coating performance product, substrate and ambient temperature should be between 20°C-25°C\* (68°F-77°F). To prevent condensation during application the surface temperature must be 3°C (5°F) or more above the dew point at all times.

\*for use outside this range please contact your Endura representative.

### Application Method

Once product is activated, do a test spray to check nozzle flow, substrate compatibility and color correctness. The spray fan can be adjusted for vertical or horizontal spray, by turning the yellow nozzle orifice. Spraying distance is 8-10 inches from the surface being painted.



### Clean Up

To prevent the nozzle from clogging, turn can upside down and spray nozzle until only propellant is being sprayed (approx 2 seconds) between uses.

When work is finished, reverse aerosol and spray valve empty. The emptied aerosols are suitable for household collection.