

## Erase

Endura Erase is a water based graffiti remover that is completely biodegradable, worker friendly, easy to apply, and environmentally safer to use. It is specifically designed to work with Endura EX-2C based topcoats to quickly and safely remove graffiti. It uses physical energy released by chemical reactions to break the bond of the graffiti, removing it from the surface.

### Product Features

- ◆ Waterborne biodegradable
- ◆ Contains No TAPs or HAPS (Toxic/Hazardous air pollutants)
- ◆ No Acid
- ◆ No phosphates and alkali hydroxides
- ◆ No lead and mercury
- ◆ No Methylene chloride and NMP

### Theoretical Solids

#### Content:

Volume: N/A

### Shelf Life\*

Single Component: (1) years

\*For unopened product.

### Appearance:

Clear with lemon scent

### Erase Flow:

low viscosity for spray

### Erase No Drip :

anti sag for vertical wall

### Test Patch

Always prepare a test patch prior to full application. This will indicate the time required for project completion and suitability of products.

The time required for penetration varies according to the types of paint, the numbers of layers to be removed, and the temperature. Most paint systems will take between 0.5-1 hour.

### Equipment

Suitable spray equipment, brush, scraper and pressure washer.

### Application Method

Apply an even layer of Endura Erase onto the coating being removed. Once applied, allow Endura Erase to penetrate into the graffiti, then scrub and remove.

When removing multiple layers of graffiti coating, the remover may lift the coating layer by layer. If this happens, remove the lifted layers and reapply.

**Do not allow the stripper to dry out.** If the remover starts to dry, reapply and allow additional time for project completion.

Removal of residue can be completed by scraper, squeegee or high pressure water wash.

### Note

Endura Erase can be frozen, it will turn back into a homogenous solution for reuse after warming up.

### WARNING!

**Harmful or fatal if swallowed. Read label and Material Safety Data Sheet prior to use.**

This product is recommended for use with Endura EX-2c based topcoats and Endura epoxy primers, it is not recommended for use with Endura Express or with other painted products.

