

Prime Lock

Endura Prime Lock is a surface pre-treatment that acts as a primer to promote good adhesion of EX-2C SFC topcoat on gameline surfaces.

Product Features

◆ Adhesion Promoter

Theoretical Solids Content:

Volume: N/A

Shelf Life*

PrimeLock base: 3 Years
PrimeLock Additive:
3 Years

*For unopened product.

Useable Life of Mixed Product:


10 Hours** @ 77°F
(25°C) and 50% RH

** After 10 hours product is no longer effective as a pre treatment.
To avoid confusion it is recommended that after mixing, the date and time should be marked directly on the Prime-Lock bottle.



Safety

SEE MSDS. Contamination may cause hazardous chemical reaction.



Mixing Ratio

Mix 100ml of Prime Lock additive to 1 Liter of Prime Lock base.

Allow a sweat in period of 5 - 10 minutes.

*Intended for use with Endura EX-2C SFC topcoat.



Application Instructions

Thoroughly shake product before applying to gameline floor surfaces.

Prime-Lock must be applied on all rubber sport floor surfaces.

On smooth surfaces apply Prime Lock with a red nylon scuff pad.

On textured surfaces Prime Lock may be applied by brush.

Prime Lock powder residue must be removed with water dampened lint free cloths. **(DO NOT** spill Prime Lock in areas that will not receive paint).

Topcoat **must** be applied **30 minutes to 1 hour** after Prime Lock has been applied. If it is not possible to topcoat within this time frame the surface must be retreated with Prime Lock.