

Retarder

Technical Data Sheet (TDS)

Product Description

An additive for use in high temperature, high humidity conditions. Used for large objects requiring extended wet film times to achieve dry spray acceptance.

Product features:

- Helps prevent solvent popping
- Helps achieve dry spray acceptance

Suitability

Endura Retarder is an additive for use with EX-2C Topcoat, EX-2C Clear 100, EX-2C Clear 221. It is formulated for use during high temperatures (over 24°C / 75°F) and/or high humidity periods (above 85%) and windy conditions.

Product Characteristics

Volume Solids: N/A

Shelf Life:

Single Component*: 3 years

*For unopened product

Mechanism

Endura Retarder slows the reaction between Component A and Component B of Endura Polyurethane Coatings. Retarder is helpful primarily in the prevention of solvent popping and to some degree to cut down dry spray during hot and/or windy conditions.

Mixing Ratio

Use 2-5% (20-50 mL) per mixed liter.

Ordering Information (sizing)

Available in Pint, Quart and Gallon Bottles. Other custom sizes may be available.

Pint Bottle [FAD0060-010]

Quart Bottle [FAD0060-020]

Gallon Bottle [FAD0060-030]

Safety Precautions

Please refer to all Safety Data Sheets (SDS) before using this product. SDS sheets can be found on our website at www.endura.ca.